

Almarde III pleated retractable insect screen "removable sash design"

Applications

Servery windows,
 Awning windows (hoppers)
 Casement windows (push-out)
 Double Hung windows

Overview

Almarde III is a stylish manually operated pleated screen best suited for recess mount applications inside the window frame or the reveal.

The screen is installed using a unique latching feature that connects the screen sash to the structure, improving installation times and allows the screen sash to be removed for cleaning.

Mesh retention clips are installed top and bottom of the mesh keeping the mesh in place in windy conditions.

This design of screen incorporates a low profile channel to the sill that can be installed using double sided tape, avoiding the need to screen fix into expensive bench tops.

The screen is smooth and easy to operate as there are no tension springs or counter balances used to operate the screen.

The sliding bar stops at any position along the opening without the need of a brake or locking system.

Almarde III is particularly suited for use on servery or Bi-fold windows or in situations where Monarch Ex cannot be installed due to height to width sash ratios:

Size Range

Single Slide - opening in one direction:	Max.	2250high x 1800wide
Double slide - opening from both sides:	Max.	2250high x 3600wide

Features

- 20mm polyester pleat
- In reveal installation
- +/- 10mm building tolerance
- Sturdy construction
- Smooth operation
- No springs or counter balances
- Stops at any position along the opening.
- Smooth and easy to open and close: The system does not require spring tensioning to operate.
- Mesh retention system
- Supplied fully manufactured ready to install

Colour Range

Standard Finishes:

White powdercoat, black powdercoat, clear anodise, light bronze anodise, dark bronze anodise and stain anodise

Powder Coat Finish

Available in most popular Interpon powdercoat colours
 Pearl and special warranty colours available upon application

Timber Glo Finish

Timber Glo is a unique range of attractive powdercoat colours that blend with timber surroundings.
 Cedar, Walnut, Oregon and Jarrah

Installation

Installation can be done in the factory or on site. Installation times depend on building in conditions and screen size. As a guide Monarch Roll can be installed in less than 5 minutes per screen. Every screen is supplied with comprehensive installation and adjustment instructions.

