

**Ez Pleat** pleated retractable insect screen  
UPVC horizontal and vertical sliding

### Applications

Bi-fold Windows  
Servery windows  
Awning windows (hoppers)  
Casement windows (push-out)  
Double Hung windows

### Overview

Ez Pleat is supplied as a “**vertical pull down**” or “**horizontal sliding**” retractable screen.

This screen is perfect for use on double hung windows, awning/casement windows and small Bi-Fold windows. Sight lines are minimal due to the 15mm pleated mesh and slim line frame design that is constructed from UPVC materials.

UPVC improves thermal efficiency and is particularly suitable for use on UPVC and thermally broken windows.

The screen is primarily designed to be face mounted using double sided adhesive tape eliminating unsightly fixings and improving installation times. Careful attention must be given to tolerances when recess mounting.

Mesh retention clips are installed top and bottom of the screen keeping the mesh in place in windy conditions.

The sliding bar stops at any position along the opening without the need of a brake or locking system.

There are no tension springs or counter balances used to retract the screen making it smooth and lite to operate.

The horizontal sliding option eliminates the need to reach up over benches or furniture making the screen particularly suited for use on servery or hard to reach windows.



### Features

- Pleated mesh
- UPVC frame
- Face mount
- No screw fixings
- Horizontal and Vertical slide
- Quick to install
- Stops at any position along the opening
- Smooth and easy to open and close

### Size Range

Single Slide - opening in one direction:	Max.	2000mm high x 1000mm wide
Double slide - opening from both sides:	Max.	2000mm high x 2000mm wide

Single Slide - opening in one direction:	Max.	1600mm high x 1300mm wide
Double slide - opening from both sides:	Max.	1600mm high x 2600mm wide

Vertical Slide- opening from top to bottom	Max.	1300mm high x 1300mm wide
--	------	---------------------------

*“For sizes outside of this range refer Almarde III or Monarch Roll”*

### Colour Range

UPVC Frame - White

For other colour options refer “Visionair”

### Installation

Installation can be done in the factory or on site. Installation times depend on building in conditions and screen size. As a guide to installation times allow 10 minutes per screen. Every screen is supplied with comprehensive installation and adjustment instructions.